

# 1205 CARRYALL

Because dirt is never in the right place

When it comes to moving dirt from one area to another, nothing beats the performance of the Model 1205 CarryAll. Equipped with a 12-foot cutting blade, the 1205 can quickly load up to 5.5 yards of material at heaped capacity and hold it for transport with the aid of its front double clam-shell door.

Height adjustment up to 18" provides precise depth control, as well as plenty of clearance when dumping loads or transporting a load over uneven terrain.

The 1205 is a nice match for your average sized farm tractor with three hydraulic remotes. Whether you use it as a box scraper, grader or earthmover, the 1205 CarryAll was built with the idea that "dirt is never in the right place."

- Four 12.5L x 15 10-ply flotation tires provide plenty of support on 8-bolt wheels and 2¾" spindles.
- A box-beam frame and tongue provide unparalleled strength and rigidity.
- The pintle hitch (rated at 68,800 lbs.) combines maximum durability and quick attachment.

- All hoses are furnished, and carry a 3,000-psi rating.
- A 4" x 16" welded hydraulic cylinder provides quick response when opening and closing the clam-shell doors.
- The standard-equipment lighting package provides added safety during transport.

SPECIFICATIONS	
Heaped Capacity	5.5 yards
Struck Capacity	4.25 yards
Cutting Width	12'
Transport Type	No dolly wheels
Hitch Type	Single-lip
Transport Width	12' 10"
Transport Height	6' 6"
Overall Length	16' 10"
Ground Clearance	18"
Cutting Edges	(2) 6' blades with 6" cutting edge
Tires	(4) 12.5L x 15, 12-ply tires
Wheels	8-bolt
Spindles	2¾"
Hubs	6,500 lbs.
Number of Hyd. Hoses	5 (2.5 sets)



Hydraulic Front Gate for Carrying Material



Hydraulic Tilt for Precise Grading



Spacious Bowl Accommodates 5.5 yds. of Material

